

ECOL MOTOR
MODEL D1S 225M1-2
TECHNICAL DATA SHEET

General Data	
Frame size	225
Housing material	Casting iron
Install model	According to the standard
Type of feet	Removable feet (Standard) Fixed feet (Optional)
Net weight	303 kg
Insulation class	F (Standard)
	H (Optional)
Protection degree	IP 55 (Standard)
	IP 56 (Optional)
Thermal protection	Without (Standard)
	Customizable (Optional)
Rotation direction	Clockwise (Standard)
	Counter clockwise (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M50x 1.5
Cooling	IC 411
Painting color	RAL 7024 (Standard)
	Customizable (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical Data		
Output	45	kW
Frequency	50	Hz
Voltage (±5%)	400	V Δ @ 50Hz
	690	V Y @ 50Hz
	480	V Δ @ 60Hz
	828	V Y @ 60Hz
Rotation speed	2930	RPM @ 50Hz
	3516	RPM @ 60Hz
Rated current	78.7	A (In) @ Δ 50Hz
	45.44	A (In) @ Y 50Hz
Starting current	7.5	xIn
Rated torque	146.67	Nm (Mn)
Starting torque	2	xMn
Breakdown torque	2.3	xMn
		IE1
Efficiency	91.7	@ 100% load
	91.4	@ 75% load
	89.7	@ 50% load
Power factor cosφ	0.9	@ 100% load

Mechanical Data		
Bearings brand	C&U	(Standard)
	Customizable	(Optional)
Bearings type	6313 C3	(DE)
	6313 C3	(NDE)
Lifetime of bearings		- hours
Allowed radial load		4201 N
Allowed axial load		40000 N
Grease type	polyurea-based grease	
Lubrication interval of NDE bearing		6500 h
Lubrication interval of DE bearing		6500 h
Moment of inertia	0.241780	Kg*m ²
Noise level	92	dB(A)

