

DIESEL ENGINE

KDG SERIES FOR GENERATOR

Model: 12KDG-565

Prime power 515.0KW(700.0HP)/1500 rpm 565.0KW(768.0HP)/1800 rpm Standby Power 565.0KW(768.0HP)/1500 rpm 627.0KW(853.0HP)/1800 rpm

- The engine performance is as per ISO 3046. Type of operation is based on ISO 8528.
- Prime power is available for an unlimited number of hours per year in a variable load application.
- The permissible average power output over 24 hours of operation shall not exceed 80% of the prime power rating.

| Engine Specifications | | Fuel System | |
|---|-----------------------------|---------------------------|---------------------------|
| V-Type, 4 stroke, water-cooled, Turbocharged, | | Injection pump | Direct Injection type |
| air-to-air intercooled. | | Governor | Electronic type |
| Combustion type | Direct injection | Feed pump | Mechanical type |
| Cylinders - Bore × stroke | 12 - 128 × 142 mm | Injection nozzle | Multi-hole type/ 0.255 mm |
| Displacement | 21,927 cc | Opening pressure | 27+0.5MPa |
| | 1-12-5-8-3-10-6-7-2- | | |
| | 11 | | |
| Firing order | -4-9 | Fuel filter | Single Stage, Paper |
| Compression ratio | 14.6:1 | Fuel Consumption | <u>.</u> |
| Dry weight | Approx. 1575 kg | Prime power at 1500rpm | 129.1 liters/h |
| Dimension(LxWxH) | 1,717 × 1,389 × 1,288 mm | Standby power at 1500rpm | 141.6 liters/h |
| Rotation | Anti-clockwise | Prime power at 1800rpm | 144.4 liters/h |
| Flywheel / Housing | SAE # 14 / # 1 | Standby power at 1800rpm | 160.2 liters/h |
| | | | |
| Cooling System | | Lubrication System | |
| Cooling method | Fresh water forced type | Lub. Oil Pan Capacity | 57.0 liters |
| Water pump | Centrifugal, Belt driven | Max. allowable Oil Temp | 120 degree C. |
| Water Capacity | 23.0 liters (engine only) | | |
| | | | Min. 300 kPa |
| Max. water Temp | 95 degree C. | Oil pressure | Max. 650 kPa |
| Cooling Fan | Blade 7EA - Ø 915 mm | | |
| | | | |
| Intake & Exhaust | | Engineering Data | |
| System Max air restriction | Class 2 kDs / District Libs | Engineering Data | 40.6 m 3/min |
| | Clean 2 kPa / Dirty 5 kPa | Combustion Air at 1500rpm | 40.6 m3/min |
| Exhaust back | Max 6 kPa | Exhaust Gas at 1500rpm | 105.8 m3/min |
| | | Combustion Air at 1800rpm | 45.7 m3/min |
| | | Exhaust Gas at 1800rpm | 118.6 m3/min |
| Electric System | | Conversion Table | |
| Charging generator | 27.5 V × 45 A | PS = kW × 1.3596 | in. = mm × 0.0394 |
| Starting motor | 24 V × 7.0 kW | psi = kg/cm2 × 14.2233 | III. – IIIII ^ 0.0337 |
| | 12 V x 2 x 120 Ah | HP= PS x 0.98635 | |
| Battery | TZ V X Z X TZU AU | пr- r3 x 0.98035 | |