

## **DIESEL ENGINE**

**Engine Specifications** 

## **KDPU** SERIES FOR INDUSTRIAL

Model: 6KDPU-230 Prime power 230.0KW(312.0HP)/2200 rpm Standby Power 253.0KW(343.0HP)/2200 rpm

- The engine performance is as per ISO 3046. Type of operation is based on ISO 8528.
- Prime power is available for an unlimited number of hours per year in a variable load application.
- The permissible average power output over 24 hours of operation shall not exceed 80% of the prime power rating.

**Fuel System** 

Engine Specifications		Fuel System	
In-Line, 4 stroke, water-cool	ed, Turbocharged	Injection pump	Direct Injection type
Combustion type	Direct injection	Governor	Electronic type
Cylinders - Bore × stroke	6 - 126 × 130 mm	Feed pump	Mechanical type
Displacement	9726 cc	Injection nozzle	Multi-hole type/ 0.255 mm
Firing order	1-5-3-6-2-4	Opening pressure	25+0.5MPa
Compression ratio	16:1	Fuel filter	Single Stage, Paper
Dry weight	Approx. 990 kg	Fuel Consumption	
Dimension(LxWxH)	1775 × 865 × 1220 mm	Prime power at 2350rpm	64.4 liters/h
Rotation	Anti-clockwise	Standby power at 2350rpm	70.8 liters/h
Flywheel / Housing	SAE # 14 / # 1		
Cooling System		Lubrication System	
0.7	Fresh water forced	,	
Cooling method	type	Lub. Oil Pan Capacity	28.0 liters
Water pump	Centrifugal, Belt driven 28.0 liters (engine	Max. allowable Oil Temp	120 degree C.
Water Capacity	only)		
			Min. 294 kPa
Max. water Temp	95 degree C.	Oil pressure	Max. 490 kPa
Cooling Fan	Blade 7EA - Ø 760 mm		
Intake & Exhaust System	Clean 2 kPa / Dirty 5	Engineering Data	
Max air restriction	kPa	Combustion Air at 2350rpm	23.50 m3/min
Exhaust back	Max 6 kPa	Exhaust Gas at 2350rpm	45.80 m3/min
Electric System		Conversion Table	
Charging generator	27.5 V × 55 A	PS = kW × 1.3596	in. = $mm \times 0.0394$
Starting motor	24 V × 7.5 kW	psi = kg/cm2 × 14.2233	
Battery	12 V x 2 x 120 Ah	HP= PS x 0.98635	

